

DATE	REV	DESCRIPTION
00-00	0	
0000		

PROJECT NOTES

REFER TO
SITE RETICULATION LAYOUT
FOR DB NAME

LEGEND	
	DISTRIBUTION BOARD - (DB.XX)
	TEL
	DATA
	KIOSK
	1x20W 220V LED OPEN TUBE LUMINAIRE
	2x20W 220V LED OPEN TUBE LUMINAIRE
	3x20W 220V LED LLB SURFACE MOUNTED LUMINAIRE
	2x20W 220V LED VAPOUR PROOF FITTING
	LED HIGHBAY
	LED BULKHEAD @2000mm AFFL
	LED FLOODLIGHT
	RED LED INDICATION LIGHT
	LED CEILING MOUNTED BULKHEAD
	LED POST TOP LUMINAIRE
	LED DOWNLIGHTER
	LIGHT SWITCH SINGLE LEVER / ONE-WAY
	LIGHT SWITCH SINGLE LEVER / TWO WAY
	KEY SWITCH
	WATERTIGHT LIGHT SWITCH
	PHOTO CELL
	SOCKET AT MOUNTING HEIGHT OF 400mm ABOVE FFL
	16A 3-PIN SOCKET + EURO OUTLET
	SOCKET AT MOUNTING HEIGHT OF 1400mm ABOVE FFL
	DOUBLE SOCKET
	SOCKET IN CEILING VOID
	DOUBLE DEDICATED SOCKET
	NORMAL SOCKET ON POWER SKIRTING
	THREE PHASE SOCKET
	WORKSTATION (16A 3-PIN + EURO SSO, DOUBLE DEDICATED 16A SSO, TEL & DATA COMBINED OUTLET) THREE SEPARATE 4x4 EAL BOXES SPACED 60mm BETWEEN EACH OTHER
	TELEPHONE OUTLET
	DATA OUTLET
	POWER SKIRTING
	GEYSER POINT
	EXTRACTOR FAN
	TWO POLE ISOLATOR
	THREE POLE ISOLATOR
	MOTION SENSOR
	NORMAL CIRCUIT
	EMERGENCY CIRCUIT
	LIGHTNING PROTECTION + EARTH SPIKE TEST JOINT @2000mm AFFL
	LIGHTNING PROTECTION BONDING
	INTERCOM BASE STATION @ 1400mm AFFL
	AIR-CONDITIONING CONTROLLER
	INTERCOM SIREN
	INTERCOM CONTROL PANEL
	ALARM KEYPAD
	ACCESS CONTROL KEYPAD
	ACCESS CONTROL PUSH BUTTON
	KEY SWITCH

