











SANITARY SCHEDULE

|  |  |   |   |  |  |   |   |
|--|--|---|---|--|--|---|---|
| SA01   | SA02   | SA03  | SA04  | SA05   | SA07   | SA08  | SA09  |
| DISABLED W.C PAN   | DISABLED BASINS  | WATER CLOSET  | TOILET PAPER HOLDER   | BASINS   | URINAL   | DUST BIN  | MIRROR  |
|    |   |   |    |   |   |    |    |
| Floor mounted paraplegic wc pan ,washdown suite colour White , comprising 90° outlet pan and matching 9 litre cistern, including lid, fitments and purpose-made chromium plated side flush lever and B2 economy double flap thermoset seat.  | wall mounted basin colour White , size 455 x 290mm with one taphole (LHS) including integrated overflow and chainstay hole, bolted to wall with 2No.10mm bolts and sealed with silicone sealant where basin meets wall with Starpillar tap with flanged backnut, manufactured in accordance with SANS 226:2004 .<br><br>15mm chrome plated elbow action raised nose pillar tap with blue indicator for cold water, manufactured in accordance with SANS 226:2004 Type 2 (BS 5412). | Close coupled washdown suite with 90 degree outlet open rim pan and matching 9 litre front single flush cistern complete with lid, fitments and flushpipe bedded to floor in 1:4 cement mortar mixture. | Chromium plated brass thief proof toilet roll holder shall be as Sample 71, screwed to hardwood or patent plastic plugs in wall. The lock system must come with a standard key that allows for opening the lid for easy toilet roll replenishment.<br><br>Per cubicle | Rectangular washhand basin, size 550 x 400mm, with one taphole for 15mm Chromium plated pillar tap with "Star" handle, one taphole stopper, integrated overflow and chainstay hole, mounted to wall on and including two proprietary semi-concealed cast iron wall brackets with 10mm bolts. | Flat back stainless steel school urinal (Franke Model TU102) or similar approved, Length 1830mm. Unit to be manufactured from Grade 304 (18/10) Stainless Steel, 0,9 mm gauge. Urinal to be supplied with built- in tipping tank and a 12 mm adjustable drip cock (inlet) which controls the automatic flushing of the urinal at regular intervals. Outlet to be situated on the left of the urinal with a recess for a 40 mm chrome plated waste outlet. Urinal to include a tiling key to sides and rear walls. The back to be fully sound deadened with vermin proof bitumastic material. | The Turin, Wilson Stone 770mm highx 450mm x 450 mm 70L capacity Wilson Stone or similar approved sandtone or grey cement with fibreglass canopy Lid<br><br>Provide for 4 in total:<br>For showers + Ablutions | Grade 304 13mm 18/10 stainless steel mirrors , size 600 x 500 x 0.3mm deep,concealed thief resistant fixings,plugged and screwed to the wall with stainless steel screws. |
| SA10   | SA11   |   |   |  |  |   |   |
| SINK   | DISABLED W.C PAN   |   |   |  |  |   |   |
|    |   |   |   |  |  |   |   |
| Sink size 600 x 500 x 300mm deep. Fitted with 150mm high splashback with boxed edges. Sink legs manufactured from 304-grade stainless steel with 4 plastic adjustable foot pieces.All sink tops manufactured from 430-grade stainless steel. | surface mounted soap dispenser 100 x134 x 304mm satin stainless steel  |   |   |  |  |   |   |