



**government
printing**

Department:
Government Printing Works
REPUBLIC OF SOUTH AFRICA

Government Printing Works

GPW HQ- GENERAL UPGRADE OF EXISTING PREMISES

GPW/HQ/2017/02

530 IRONMONGERY SCHEDULE

ISSUED FOR TENDER - T

PREPARED BY



Head Office: 21 West Riding Row, Sherwood, Durban, 4091
Tel: (+27 31) 207 1340, dbn@ldm.co.za
PTA Office: 239 Lange Street, Neuw Muckleneuk Street, Brooklyn,
Pretoria 0180, Tel: (+27 12) 346 8676
JHB Office: Suite 13, 1st Floor, Katherine & West, 114 West Street,
Sandown, 2196, (+27 11) 442 0754



PROJECT NAME: Government Printing Works Timber Doors

PROFESSIONAL: PGA Architects

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

REPORT DATE: 09/11/2020

dormakaba 

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors





REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		01			
Hardware Set Quantity :		1			
Notes					
Doors (1)		-1.02			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DDC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Double Cylinder Key to Differ	Satin Nickel	1	Each

HARDWARE FOR SET:		02			
Hardware Set Quantity :		1			
Notes					
Doors (2)		-1.03, -1.24			
Product Image	Product Code	Description	Finish	Qty	Units
	IBTDM	Ironmongery by Transformer door manufacturer		1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors









REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		03			
Hardware Set Quantity :		1			
Notes					
Doors (5)		-1.04, -1.05, -1.30, 0.45, 0.46			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	2	Pair
	DRP-SS-023	dormakaba 62x44mm Ring Flush Pull Handle	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DSC054301 KD (43mm)	dormakaba 43mm five pin Euro-profile Single Cylinder Key to Differ	Satin Nickel	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	0.5	Pair
	D038R NP	dormakaba Rebate conversion kit for Euro Profile locks D036S, D037D.	Nickel Plated	1	Each
	DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	2	Each
	DSS-136 EL	dormakaba 150x150mm ELECTRICAL sign	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors







REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		04			
Hardware Set Quantity :		1			
Notes					
Doors (1)		-1.06			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS93B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	ACBSS	Access control by security specialist		1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors






REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		05			
Hardware Set Quantity :		1			
Notes					
Doors (1)		-1.07			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS93G - AB - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Push-side door leaf fixing (Standard), Pull-side transom fixing.(Angle bracket included). Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	ACBSS	Access control by security specialist		1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors





REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		06			
Hardware Set Quantity :		1			
Notes					
Doors (1)		-1.08			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1	Pair
	DRP-SS-023	dormakaba 62x44mm Ring Flush Pull Handle	Stainless Steel	1	Each
	DBC-SS-022	dormakaba Adjustable Roller Bolt	Stainless Steel	1	Each
	DSS-145 FHR	dormakaba 150x150mm FIRE HOSE REEL sign	Stainless Steel	1	Each
	DSS-146 FE	dormakaba 150x150mm FIRE EXTINGUISHER sign	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		07			
Hardware Set Quantity :		1			
Notes					
Doors (4)		-1.09, -1.13, -1.17, -1.23			
Product Image	Product Code	Description	Finish	Qty	Units
	HBSFM	Hinges by Steel frame manufacturer		0	Each
	TS93B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Double Cylinder Key to Differ	Nickel Plated	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors






REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		08			
Hardware Set Quantity :		1			
Notes					
Doors (4)		-1.10, -1.12, 0.27, 5.06			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1	Pair
	SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DDC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Double Cylinder Key to Differ	Satin Nickel	1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors





REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		09			
Hardware Set Quantity :		1			
Notes					
Doors (2)		-1.19, -1.22			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1	Pair
	DWC-005	dormakaba Bathroom WC indicator (Red and White) and turnknob	Stainless Steel	1	Set
	D032D SS	dormakaba Bathroom Deadlock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DHC-SS-031B	dormakaba Hat and Coat Hook with rubber buffer	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		10			
Hardware Set Quantity :		1			
Notes					
Doors (1)		-1.20			
Product Image	Product Code	Description	Finish	Qty	Units
	HBFMF	Hinges by fire door manufacturer		1	Each
	TS93B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		2	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Double Cylinder Key to Differ	Nickel Plated	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DSS-131 F	dormakaba 150x150mm FEMALE sign	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		11			
Hardware Set Quantity :		1			
Notes					
Doors (1)		-1.21			
Product Image	Product Code	Description	Finish	Qty	Units
	HBFMF	Hinges by fire door manufacturer		1	Each
	TS93B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		2	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Double Cylinder Key to Differ	Nickel Plated	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DSS-130 M	dormakaba 150x150mm MALE sign	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors







REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		12			
Hardware Set Quantity :		1			
Notes					
Doors (3)		-1.26, -1.27, -1.28			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	3	Pair
	SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DDC056601 KA (66mm)	dormakaba 66mm five pin Euro-profile Double Cylinder Keyed Alike	Satin Nickel	1	Each
	D038R NP	dormakaba Rebate conversion kit for Euro Profile locks D036S, D037D.	Nickel Plated	1	Each
	DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	2	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors






REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		13			
Hardware Set Quantity :		1			
Notes					
Doors (23)		-1.29, 0.01, 0.51, 1.02, 1.03, 1.18, 1.24, 2.02, 2.03, 2.20, 2.26, 3.02, 3.03, 3.18, 3.24, 4.02, 4.03, 4.18, 4.24, 5.02, 5.03, 5.19, 5.25			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1	Pair
	DRP-SS-023	dormakaba 62x44mm Ring Flush Pull Handle	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DSC054301 KD (43mm)	dormakaba 43mm five pin Euro-profile Single Cylinder Key to Differ	Satin Nickel	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	0.5	Pair

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors







REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		14			
Hardware Set Quantity :		1			
Notes					
Doors (10)		-1.31, 0.03, 0.16, 0.20, 0.47, 1.46, 2.46, 3.45, 4.44, 5.46			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors




REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		15			
Hardware Set Quantity :		1			
Notes		Solid door required for paraplegic application			
Doors (1)		0.07			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	DPH301B	dormakaba 325x25mm Straight Tubular Pull Handle Flange Fixing	Stainless Steel	2	Each
	DWC-006	dormakaba Disabled WC indicator (Red & White) and turnknob for physically impaired	Stainless Steel	1	Set
	D032D SS	dormakaba Bathroom Deadlock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DBC-SS-022	dormakaba Adjustable Roller Bolt	Stainless Steel	1	Each
	DGR-SS-151	dormakaba 800x80mm Flush valve Back Rail	Stainless Steel	1	Each
	DGR-SS-152	dormakaba 300x300x300mm Side Grab Rail	Stainless Steel	1	Each
	250 x width kick	250mm x width of door x 2mm grade 304 s/s kick plate. 1 hole lasered every 200mm for countersunk fixings		2	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DSS-133 P	dormakaba 150x150mm DISABLED PERSONS sign	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		16			
Hardware Set Quantity :		1			
Notes					
Doors (7)		0.08, 0.40, 1.29, 2.31, 3.29, 4.29, 5.30			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	DPH205 BTB	dormakaba 400x30mm Straight Tubular Pull Handle BTB (BTB Fixing Sets included)	Stainless Steel	1	Pair
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Double Cylinder Key to Differ	Satin Nickel	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	250 x width kick	250mm x width of door x 2mm grade 304 s/s kick plate. 1 hole lasered every 200mm for countersunk fixings		2	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors


REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Image	Product Code	Description	Finish	Qty	Units
	DSS-130 M	dormakaba 150x150mm MALE sign	Stainless Steel	1	Each

HARDWARE FOR SET:	17
Hardware Set Quantity :	1
Notes	
Doors (7)	0.09, 0.39, 1.19, 2.21, 3.19, 4.19, 5.20

Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	DPH205 BTB	dormakaba 400x30mm Straight Tubular Pull Handle BTB (BTB Fixing Sets included)	Stainless Steel	1	Pair
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Double Cylinder Key to Differ	Satin Nickel	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors



REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects







REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Image	Product Code	Description	Finish	Qty	Units
	250 x width kick	250mm x width of door x 2mm grade 304 s/s kick plate. 1 hole lasered every 200mm for countersunk fixings		2	Each
	DSS-131 F	dormakaba 150x150mm FEMALE sign	Stainless Steel	1	Each

HARDWARE FOR SET:	18
Hardware Set Quantity :	1
Notes	
Doors (3)	0.15, 4.48, 4.49

Product Image	Product Code	Description	Finish	Qty	Units
	HBFMF	Hinges by fire door manufacturer		1	Each
	TS92B G-SR	dormakaba NON HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-2200mm. Closing Force EN 2-4. Adjustable strength. Hydraulic speed control. Max door width 1100mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DKC058001 KA (80mm)	dormakaba 80mm five pin Euro-profile Knob Cylinder Keyed Alike	Satin Nickel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors





REPORT DATE: 09/11/2020



PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Image	Product Code	Description	Finish	Qty	Units
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	2	Each
	DPS-SS-032	dormakaba Dust Proof Strike	Stainless Steel	1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop NOTE: Door stop to be screwed to floor in sensible position to allow maximum opening	Stainless Steel	1	Each

HARDWARE FOR SET:		19			
Hardware Set Quantity :		1			
Notes		Steel door to be primed and painted before ironmongery is fitted.			
Doors (1)		0.17			
Product Image	Product Code	Description	Finish	Qty	Units
	HBSFM	Hinges by Steel frame manufacturer		1	Each
	TS93G - AB - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Push-side door leaf fixing (Standard), Pull-side transom fixing.(Angle bracket included). Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	PHB2 W SD	dormakaba Two point locking panic bar - Single door - Door leaf 1300mm wide x 2270mm high (3103. PHX02. PHX04)	-	1	Set

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors








REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		20			
Hardware Set Quantity :		1			
Notes					
Doors (1)		0.18			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	3	Pair
	SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DDC056601 KA (66mm)	dormakaba 66mm five pin Euro-profile Double Cylinder Keyed Alike	Satin Nickel	1	Each
	D038R NP	dormakaba Rebate conversion kit for Euro Profile locks D036S, D037D.	Nickel Plated	1	Each
	DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	2	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors





REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		21			
Hardware Set Quantity :		1			
Notes					
Doors (1)		0.19			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	PHB1 S SD	dormakaba One point locking panic bar - Single door - Door leaf 1000mm wide (3101)	-	1	Set
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors








REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		22			
Hardware Set Quantity :		1			
Notes		Steel door to be primed and paitned before ironmongery is fitted.			
Doors (1)		0.35			
Product Image	Product Code	Description	Finish	Qty	Units
	HBSFM	Hinges by Steel frame manufacturer		1	Each
	TS93G - AB - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Push-side door leaf fixing (Standard), Pull-side transom fixing.(Angle bracket included). Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DKC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Knob Cylinder Key to Differ	Satin Nickel	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors







REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		23			
Hardware Set Quantity :		1			
Notes					
Doors (1)		0.36			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	ACBSS	Access control by security specialist		1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		24			
Hardware Set Quantity :		1			
Notes					
Doors (12)		0.37, 1.15, 1.31, 2.17, 2.33, 3.15, 3.31, 3.47, 4.15, 4.31, 5.16, 5.32			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DKC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Knob Cylinder Key to Differ	Nickel Plated	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors





REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		25			
Hardware Set Quantity :		1			
Notes					
Doors (1)		0.64			
Product Image	Product Code	Description	Finish	Qty	Units
	HBFMF	Hinges by fire door manufacturer		1	Each
	TS92B G-SR EMF 1	dormakaba ELECTRO MECHANICAL HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-2200mm. Closing Force EN 2-4. Adjustable strength. Hydraulic speed control. Max door width 1100mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	2	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		2	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	2	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors









REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		27			
Hardware Set Quantity :		1			
Notes					
Doors (5)		1.17, 2.19, 3.17, 4.17, 5.18			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	3	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	ACBSS	Access control by security specialist		1	Each
	DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	2	Each
	DPS-SS-032	dormakaba Dust Proof Strike	Stainless Steel	1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors







REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		28			
Hardware Set Quantity :		1			
Notes		These doors specifically requested not to have a door closer but to have restricted signage sign.			
Doors (5)		1.32, 2.34, 3.32, 4.32, 5.33			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DDC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Double Cylinder Key to Differ	Nickel Plated	1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	Restricted signage	Signage with Restricted Access to be provided by others for fire doors without door closers as per Mechanical Engineer		1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors







REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		30			
Hardware Set Quantity :		1			
Notes					
Doors (2)		3.53, 3.54			
Product Image	Product Code	Description	Finish	Qty	Units
	HBFMF	Hinges by fire door manufacturer		1	Each
	TS92B G-SR	dormakaba NON HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-2200mm. Closing Force EN 2-4. Adjustable strength. Hydraulic speed control. Max door width 1100mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	ACBSS	Access control by security specialist		1	Each
	DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	2	Each
	DPS-SS-032	dormakaba Dust Proof Strike	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors






REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		31			
Hardware Set Quantity :		1			
Notes					
Doors (1)		5.09			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1	Pair
	SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DBC006601	dormakaba 66mm Euro-profile Bathroom / Privacy Cylinder	Satin Nickel	1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		32			
Hardware Set Quantity :		1			
Notes					
Doors (1)		6.01			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS93G - AB - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Push-side door leaf fixing (Standard), Pull-side transom fixing.(Angle bracket included). Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Double Cylinder Key to Differ	Nickel Plated	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors


REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		33			
Hardware Set Quantity :		1			
Notes					
Doors (1)		6.02			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS93B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Double Cylinder Key to Differ	Nickel Plated	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors





REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		34			
Hardware Set Quantity :		1			
Notes					
Doors (1)		6.03			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1	Pair
	SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DDC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Double Cylinder Key to Differ	Satin Nickel	1	Each
	CHBO	Cabin Hooks by other		1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors







REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		26			
Hardware Set Quantity :		1			
Notes					
Doors (5)		1.16, 2.18, 3.16, 4.16, 5.17			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	1.5	Pair
	TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Each
	PHB1 S SD	dormakaba One point locking panic bar - Single door - Door leaf 1000mm wide (3101)	-	1	Set
	PHT3901	dormakaba Exterior access lock with lever handle (Cylinder not included)	Satin Nickel	1	Each
	DSC054501 KA (45mm)	dormakaba 45mm five pin Euro-profile Single Cylinder Keyed Alike NOTE: NB: Single Cylinder. Do not drill all the way through the door	Satin Nickel	1	Each
	DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

HARDWARE PER SET

PROJECT NAME: Government Printing Works Timber Doors










REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

HARDWARE FOR SET:		29			
Hardware Set Quantity :		1			
Notes					
Doors (2)		2.53, 2.54			
Product Image	Product Code	Description	Finish	Qty	Units
	HBFMF	Hinges by fire door manufacturer		1	Each
	TS92B G-SR	dormakaba NON HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-2200mm. Closing Force EN 2-4. Adjustable strength. Hydraulic speed control. Max door width 1100mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	1	Each
	400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		1	Each
	DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	1	Each
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DKC058001 KA (80mm)	dormakaba 80mm five pin Euro-profile Knob Cylinder Keyed Alike	Satin Nickel	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	2	Each
	DPS-SS-032	dormakaba Dust Proof Strike	Stainless Steel	1	Each

CONTROL LIST

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Door Number	Hardware Set	Area	Location	Door Type	Handing	GMK	MK	KA
-1.02	01	Basement	AC Room	ED04	LH			
-1.03	02	Basement	H T Room	SD02	DD			
-1.04	03	Basement	Service Duct	ED03A	DD			
-1.05	03	Basement	Service Duct	ED03A	DD			
-1.06	04	Basement	Stair 2	ED05	RH			
-1.07	05	Basement	Lift Lobby	ED05	RH			
-1.08	06	Basement	FHR	ED02	RH			
-1.09	07	Basement	Electrical Room	FD01	LH			
-1.10	08	Basement	Unknown	ED14	RH			
-1.12	08	Basement	Security Green Room	TD01	RH			
-1.13	07	Basement	Security Green Room	SD01	LH			
-1.17	07	Basement	Security Booth	SD01	LH			
-1.19	09	Basement	W C Cubicle	TD09	LH			
-1.20	10	Basement	Female Locker Room	SD01	RH			
-1.21	11	Basement	Male Locker Room	SD01	LH			
-1.22	09	Basement	W C Cubicle	TD09	RH			
-1.23	07	Basement	Security Store	SD01	LH			
-1.24	02	Basement	Mechanical Room	SD02	DD			
-1.26	12	Basement	Standby Motor room	ED01	DD			
-1.27	12	Basement	Transformer Room	ED01	DD			
-1.28	12	Basement	L V Room	ED01	DD			
-1.29	13	Basement	Duct	ED02	LH			
-1.30	03	Basement	Service Duct	ED03	DD			
-1.31	14	Basement	Stair 1	ED05	LH			
0.01	13	Gr Floor	Duct	ED12	LH			
0.03	14	Gr Floor	Refuse	FD01	LH			
0.07	15	Gr Floor	Paraplegic	TD03	RH			
0.08	16	Gr Floor	Male Visitors	TD02	LH			
0.09	17	Gr Floor	Female Visitors	TD02	RH			
0.15	18	Gr Floor	Archive Storage	FD03	DD			
0.16	14	Gr Floor	Stair 2	ED05	LH			
0.17	19	Gr Floor	Fire Escape	ED08	LH			
0.18	20	Gr Floor	H T Room	ED01	DD			
0.19	21	Gr Floor	Stair 2	ED05	RH			
0.20	14	Gr Floor	Stair 2	ED05	RH			
0.27	08	Gr Floor	Plant Room	TD04	RH			
0.35	22	Gr Floor	Security Access	ED08	RH			

CONTROL LIST

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Door Number	Hardware Set	Area	Location	Door Type	Handing	GMK	MK	KA
0.36	23	Gr Floor	Security Monitoring	TD04	RH			
0.37	24	Gr Floor	Patch Room	FD01	RH			
0.39	17	Gr Floor	Female Staff	TD02	RH			
0.40	16	Gr Floor	Male Staff	TD02	RH			
0.45	03	Gr Floor	Service Duct	ED06	DD			
0.46	03	Gr Floor	Service Duct	ED06	DD			
0.47	14	Gr Floor	Stair 1	ED05	RH			
0.51	13	Gr Floor	Duct	DD01	LH			
0.64	25	Gr Floor	Lift Lobby	FD02	DD			
1.02	13	1st Floor	Duct	DD03	LH			
1.03	13	1st Floor	Duct	DD03	LH			
1.15	24	1st Floor	Plant Room	ED05	LH			
1.16	26	1st Floor	Stair 2	ED05	RH			
1.17	27	1st Floor	Lift Lobby	ED09	DD			
1.18	13	1st Floor	Duct	ED11	LH			
1.19	17	1st Floor	Female Staff	TD02	RH			
1.24	13	1st Floor	Duct	DD01	LH			
1.29	16	1st Floor	Male Staff	TD02	RH			
1.31	24	1st Floor	Patch Room	FD01	LH			
1.32	28	1st Floor	Plant Room	FD01	RH			
1.46	14	1st Floor	Stair 1	ED05	RH			
2.02	13	2nd Floor	Duct	DD03	LH			
2.03	13	2nd Floor	Duct	DD03	LH			
2.17	24	2nd Floor	Plant Room	ED05	LH			
2.18	26	2nd Floor	Stair 2	ED05	RH			
2.19	27	2nd Floor	Lift Lobby	ED09	DD			
2.20	13	2nd Floor	Duct	ED11	LH			
2.21	17	2nd Floor	Female Staff	TD02	RH			
2.26	13	2nd Floor	Duct	DD01	LH			
2.31	16	2nd Floor	Male Staff	TD02	RH			
2.33	24	2nd Floor	Patch Room	FD01	LH			
2.34	28	2nd Floor	Plant Room	FD01	RH			
2.46	14	2nd Floor	Stair 1	ED05	RH			
2.53	29	2nd Floor	Server Test Room	FD02	DD			
2.54	29	2nd Floor	Server Room	FD02	DD			
3.02	13	3rd Floor	Duct	DD03	LH			
3.03	13	3rd Floor	Duct	DD03	LH			

CONTROL LIST

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Door Number	Hardware Set	Area	Location	Door Type	Handing	GMK	MK	KA
3.15	24	3rd Floor	Plant Room	ED05	LH			
3.16	26	3rd Floor	Stair 2	ED05	RH			
3.17	27	3rd Floor	Lift Lobby	ED09	DD			
3.18	13	3rd Floor	Duct	ED11	LH			
3.19	17	3rd Floor	Female Staff	TD02	RH			
3.24	13	3rd Floor	Duct	DD01	LH			
3.29	16	3rd Floor	Male Staff	TD02	RH			
3.31	24	3rd Floor	Patch Room	FD01	LH			
3.32	28	3rd Floor	Plant Room	FD01	RH			
3.45	14	3rd Floor	Stair 1	ED05	RH			
3.47	24	3rd Floor	Forensics Lab	FD01	LH			
3.53	30	3rd Floor	Sensitive Storage	FD03	DD			
3.54	30	3rd Floor	Sensitive Storage	FD03	DD			
4.02	13	4th Floor	Duct	DD03	LH			
4.03	13	4th Floor	Duct	DD03	LH			
4.15	24	4th Floor	Plant Room	ED05	LH			
4.16	26	4th Floor	Stair 2	ED05	RH			
4.17	27	4th Floor	Lift Lobby	ED09	DD			
4.18	13	4th Floor	Duct	ED11	LH			
4.19	17	4th Floor	Male Staff	TD02	RH			
4.24	13	4th Floor	Duct	DD01	LH			
4.29	16	4th Floor	Male Staff	TD02	RH			
4.31	24	4th Floor	Patch Room	FD01	LH			
4.32	28	4th Floor	Plant Room	FD01	RH			
4.44	14	4th Floor	Stair 1	ED05	RH			
4.48	18	4th Floor	Archive Storage 2	FD03	DD			
4.49	18	4th Floor	Archive Storage 1	FD03	DD			
5.02	13	5th Floor	Duct	DD03	LH			
5.03	13	5th Floor	Duct	DD03	LH			
5.06	08	5th Floor	10 Seater B Room	TD01	LH			
5.09	31	5th Floor	Office 1 WC	TD01	RH			
5.16	24	5th Floor	Plant Room	ED05	LH			
5.17	26	5th Floor	Stair 2	ED05	RH			
5.18	27	5th Floor	Lift Lobby	ED09	DD			
5.19	13	5th Floor	Duct	ED11	LH			
5.20	17	5th Floor	Female Staff	TD02	RH			
5.25	13	5th Floor	Duct	DD01	LH			

CONTROL LIST

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Door Number	Hardware Set	Area	Location	Door Type	Handing	GMK	MK	KA
5.30	16	5th Floor	Male Staff	TD02	RH			
5.32	24	5th Floor	Patch Room	FD01	LH			
5.33	28	5th Floor	Plant Room	FD01	RH			
5.46	14	5th Floor	Stair 1	ED05	RH			
6.01	32	6th Floor	Roof Access	ED05	LH			
6.02	33	6th Floor	Roof Access	ED05	RH			
6.03	34	6th Floor	Roof Access	ED14	RH			

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Code	Description	Finish	Units	Qty	Price	Total
DBB-SS-009	dormakaba 102x75x3mm Two Ball Bearing Butt Hinge	Stainless Steel	Pair	150.0		
SH815 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	Set	16.0		
D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	Each	16.0		
DDC056601 KA (66mm)	dormakaba 66mm five pin Euro-profile Double Cylinder Keyed Alike	Satin Nickel	Each	4.0		
DDS-SS-021	dormakaba Floor Mounted Door Stop	Stainless Steel	Each	72.0		
D038R NP	dormakaba Rebate conversion kit for Euro Profile locks D036S, D037D.	Nickel Plated	Each	9.0		
DFB-SC-180	dormakaba 153mm Manual flush bolt with heel	Satin Chrome	Each	42.0		
DDC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Double Cylinder Key to Differ	Satin Nickel	Each	20.0		
400 x 75 back	400mm x 75mm x 2mm grade 304 s/s back plate with 6 holes lasered for countersunk fixings. 2 only 8mm diameter holes lasered for dormakaba fixings. Bolts to fit through plate and door.		Each	64.0		
DPH205 BTB	dormakaba 400x30mm Straight Tubular Pull Handle BTB (BTB Fixing Sets included)	Stainless Steel	Pair	14.0		
TS92B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1100mm. Closing Force EN 2-4V. Adjustable strength. Hydraulic speed control. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	Each	48.0		
D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	Each	68.0		

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Code	Description	Finish	Units	Qty	Price	Total
DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	Pair	54.0		
400 x 150 push 304	dormakaba 400mm x 150mm x 2mm grade 304 s/s push plate with 6 holes lasered for countersunk fixings.	-	Each	62.0		
DSS-130 M	dormakaba 150x150mm MALE sign	Stainless Steel	Each	8.0		
250 x width kick	250mm x width of door x 2mm grade 304 s/s kick plate. 1 hole lasered every 200mm for countersunk fixings		Each	30.0		
HBFMF	Hinges by fire door manufacturer		Each	10.0		
DPS-SS-032	dormakaba Dust Proof Strike	Stainless Steel	Each	12.0		
DKC058001 KA (80mm)	dormakaba 80mm five pin Euro-profile Knob Cylinder Keyed Alike	Satin Nickel	Each	5.0		
DPH205 BT	dormakaba 400x30mm Straight Tubular Pull Handle BT	Stainless Steel	Each	48.0		
TS92B G-SR	dormakaba NON HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-2200mm. Closing Force EN 2-4. Adjustable strength. Hydraulic speed control. Max door width 1100mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	Set	7.0		
DPH301B	dormakaba 325x25mm Straight Tubular Pull Handle Flange Fixing	Stainless Steel	Each	2.0		
DWC-006	dormakaba Disabled WC indicator (Red & White) and turnknob for physically impaired	Stainless Steel	Set	1.0		
D032D SS	dormakaba Bathroom Deadlock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm.	Stainless Steel	Each	3.0		

BILL OF MATERIALS



PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Code	Description	Finish	Units	Qty	Price	Total
DBC-SS-022	dormakaba Adjustable Roller Bolt	Stainless Steel	Each	2.0		
DGR-SS-151	dormakaba 800x80mm Flush valve Back Rail	Stainless Steel	Each	1.0		
DGR-SS-152	dormakaba 300x300x300mm Side Grab Rail	Stainless Steel	Each	1.0		
DSS-133 P	dormakaba 150x150mm DISABLED PERSONS sign	Stainless Steel	Each	1.0		
DRP-SS-023	dormakaba 62x44mm Ring Flush Pull Handle	Stainless Steel	Each	29.0		
DSC054301 KD (43mm)	dormakaba 43mm five pin Euro-profile Single Cylinder Key to Differ	Satin Nickel	Each	28.0		
DWC-005	dormakaba Bathroom WC indicator (Red and White) and turnknob	Stainless Steel	Set	2.0		
DHC-SS-031B	dormakaba Hat and Coat Hook with rubber buffer	Stainless Steel	Each	2.0		
DKC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Knob Cylinder Key to Differ	Nickel Plated	Each	12.0		
DSS-131 F	dormakaba 150x150mm FEMALE sign	Stainless Steel	Each	8.0		
DSS-136 EL	dormakaba 150x150mm ELECTRICAL sign	Stainless Steel	Each	5.0		
DDC058001 KD (80mm)	dormakaba 80mm five pin Euro-profile Double Cylinder Key to Differ	Nickel Plated	Each	13.0		

BILL OF MATERIALS

PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Code	Description	Finish	Units	Qty	Price	Total
TS93B - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Pull-side door leaf fixing (Standard), Push-side transom fixing. Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	Each	8.0		
HBSFM	Hinges by Steel frame manufacturer		Each	2.0		
ACBSS	Access control by security specialist		Each	10.0		
DSS-145 FHR	dormakaba 150x150mm FIRE HOSE REEL sign	Stainless Steel	Each	1.0		
DSS-146 FE	dormakaba 150x150mm FIRE EXTINGUISHER sign	Stainless Steel	Each	1.0		
TS93G - AB - SL	dormakaba NON HOLD OPEN Cam action slide channel door closer. Max door width 1250mm. Closing Force EN 2-5V. Adjustable strength. Hydraulic speed control. Backcheck. Delayed action. Push-side door leaf fixing (Standard), Pull-side transom fixing.(Angle bracket included). Door closer compliant with EN 1154. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	Set	4.0		
PHB1 S SD	dormakaba One point locking panic bar - Single door - Door leaf 1000mm wide (3101)	-	Set	6.0		
CHBO	Cabin Hooks by other		Each	1.0		
PHB2 W SD	dormakaba Two point locking panic bar - Single door - Door leaf 1300mm wide x 2270mm high (3103. PHX02. PHX04)	-	Set	1.0		
DKC056501 KD (65mm)	dormakaba 65mm five pin Euro-profile Knob Cylinder Key to Differ	Satin Nickel	Each	1.0		
DBC006601	dormakaba 66mm Euro-profile Bathroom / Privacy Cylinder	Satin Nickel	Each	1.0		
IBTDM	Ironmongery by Transformer door manufacturer		Each	2.0		

BILL OF MATERIALS



PROJECT NAME: Government Printing Works Timber Doors

REPORT DATE: 09/11/2020

PROFESSIONAL: PGA Architects

REVISION DATE: 05/11/2020

CONSULTANT: Ursula Jansen (082 577 1345)

REVISION: v 4

Product Code	Description	Finish	Units	Qty	Price	Total
Restricted signage	Signage with Restricted Access to be provided by others for fire doors without door closers as per Mechanical Engineer		Each	5.0		
TS92B G-SR EMF 1	dormakaba ELECTRO MECHANICAL HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-2200mm. Closing Force EN 2-4. Adjustable strength. Hydraulic speed control. Max door width 1100mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	Set	1.0		
PHT3901	dormakaba Exterior access lock with lever handle (Cylinder not included)	Satin Nickel	Each	5.0		
DSC054501 KA (45mm)	dormakaba 45mm five pin Euro-profile Single Cylinder Keyed Alike	Satin Nickel	Each	5.0		
Total						

ALL PRODUCTS, PRODUCT SPECIFICATIONS, PRICES AND DATA SHEETS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

dormakaba South Africa Pty Ltd, and its employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any specification document or in any other disclosure relating to any product.

dormakaba South Africa Pty Ltd makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

To the maximum extent permitted by applicable law, dormakaba South Africa Pty Ltd disclaims

- i. any and all liability arising out of the application or use of any product,
- ii. any and all liability, including without limitation special, consequential or incidental damages, and
- iii. any and all implied warranties, including warranties of fitness for particular purpose, non infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on dormakaba South Africa Pty Ltd knowledge of typical requirements that are often placed on dormakaba products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Product specifications do not expand or otherwise modify dormakaba South Africa Pty Ltd terms and conditions of purchase, including but not limited to the warranty expressed therein.

Customers using or selling dormakaba products not expressly indicated for use in such applications do so at their own risk.

Please contact authorized dormakaba personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of dormakaba South Africa Pty Ltd.

Product names and markings noted herein may be trademarks of their respective owners.