[illegible]

SECTION A - A
SCALE - 1:100

100mm non-combustible lightweight fibreglass insulation blanket fitted between the beams and laid loose on top of bracing.

Beam filling.

Aluminum barge board.

Brick on edge lintel.

330mm x 330mm brick columns to Str. Eng. details.

Conc. rainwater channel as per Str. Eng. details.

NGL

Conc. raft foundation to Str. Eng. details.

Reinforced concrete foundation to Engineer's details to suit the specific site conditions.

VERANDAH

DPC

PLASTER & PAINT

DPC

DPC

DPC

DPC

DPC

Salotek 700 compatible root sheeting

75mm gypsum covered cornice nailed to wall and ceiling.

38mm x 114mm wallplate.

Beam filling.

Aluminum barge board.

500

2.105

2.805

WALLPLATE LEVEL +2.805

U/S LINTOL LEVEL +2.805

TOP OF SLAB LEVEL +0.170

NGL



New wall tiles to 1800mm high with plaster and paint above tiling.

New tiles on 30mm screed on new Reinforced Conc. floor slab as per Str. Eng. details.

Conc. rainwater channel as per Str. Eng. details.

Facebrick on edge lintel.

SECTION B - B
SCALE - 1:100



FRONT ELEVATION
SCALE - 1:100

SANITARY FITTINGS	STANDARD WC	WC SILENT: 1/2" W/1/2" brass chain and pin P/30g with white heavy duty single plastic top seat. If the pin hole white, white chain carry with white fitting and matching brass pin. Flush Mount. System to be utilized if any water pressure added.
	PARALEPIC WC	Black metal 1/2" w/ hung open top seat. To be used with a concealed cistern or in a suitable base for a cistern.
	WALL URINAL	STAINLESS STEEL CURVED BACK URINAL: TO SUIT THE WALL LENGTHS comply with concealed square pipe with 1/2 or 3/4" Nuts/pipe couplings one 1/2" from cistern outlet with grating
	WHITE PORCELAIN ENAMELED BACINS with one hole pre-drilled	31 mm chromium plated outlet, with plug, chain, anchor & 25mm back connect. Provide one chromium plated top seat except in AIRMEN Club & Grade 9's Club room except for the bar. 1/2" Nuts/pipe couplings one 1/2" from back connect. Provide black cover pin P/30g. Disassembled White top & 25mm 1/4000.
	WHITE GLAZED PORCELAIN WHB	COMB W/ATER/CELF plug pin no 1/11" wall stud chromium plated handle, color matching. (bushings to be supplied) 1/2" Nuts/pipe couplings 400psi (4 bar) accessories to manufacturer specification
	TAPS	Frankel 1.5mm 1/10" stainless steel rimmed or 500 x 500 with a reflective polished surface and concealed fast restangings. 1 vmm or basic
	MIRROR	Frankel TR2 stainless steel wall mounted double toilet roller 500 x 140 x 136 mm
	ROLL HOLDER	Rainbow Cisterns: Ref TR2 200gms galvanized with 1 1/2" legs. 200 1/400 quality stainless steel 20mm out. Finish satin polished. 50mm slot hinges drilled and countersunk with 1/2" screw.
PARALEPIC WC GRABRAILS		Rainbow Grabrails: Ref TR2 200gms 200mm straight galvanized galvanized or as specified Cisterns. 200 1/400 quality stainless steel 20mm out. Finish satin polished. 50mm slot hinges drilled and countersunk with 1/2" screw.

NOTES:

1. All boundaries, dimensions and levels are to be checked on site before construction and any discrepancies are to be reported to the office of the Architect.
2. Partial Service: Any discrepancies with site or other information is to be advised to the Architect and direction or approval is to be sought before the implementation of the detail.
3. Do not scale this drawing.
4. For the purpose of coordination, all relevant parties must check this information prior to implementation and report any discrepancies to the Architect.

[illegible]

Architect :

Name :

Signature :

Client :

Signature :



Project:

**CONDITION ASSESSMENT
POPANO SECONDARY SCHOOL**

Drawing description:

**PROPOSED NEW x3 CLASSROOMS
BLOCK (WITH ABLUTIONS)
(BLOCKS E & G)**

Drawn:
ISENZEKO ENGINEERING

A1

Scale/s: AS SHOWN ON DRAWING

FOR INFORMATION

Drawing Number:

082-PSS-ND-104

Revision: